Application Serial No. 10/563,412 Response to Office Action

Listing of Claims:

5

10

Claims 1-4 (Canceled).

- 5. (Previously Presented) A method of detecting fatigue crack in a base material, said method comprising:
- (a) preparing a paste in which particles having a hardness not less than a hardness of the base material and an oil having viscosity are mixed with each other;
- (b) applying said paste to a desired portion of said base material; and
- (c) detecting fatigue crack based on a change in color generated by movement of base material powder to a surface of said paste, said base material powder being produced when said base material at a surface of the fatigue crack is ground in contact with said particles due to opening and closing of the fatigue crack in said base material.
- 6. (Previously Presented) A method of detecting fatigue crack according to claim 5, wherein said particles comprise light-colored ceramics including white ceramics.
- (Previously Presented) A method of detecting fatigue crack according to claim 5, wherein preparing the paste

Application Serial No. 10/563,412 Response to Office Action

comprises:

5

5

adjusting the oil to have a viscosity of 5,000 centipoises to 15,000 centipoises; and

mixing said particles into the adjusted oil.

8. (Previously Presented) A method of detecting fatigue crack according to claim 6, wherein preparing the paste comprises:

adjusting the oil to have a viscosity of 5,000 centipoises to 15,000 centipoises; and

mixing said particles into the adjusted oil.

- 9. (Currently Amended) A paste to be applied to a desired portion of a base material for at least one of restraining fatigue crack growth in said base material and detecting fatigue crack in said base material, said paste comprising:
- particles having diameters of 2 µm to 40 µm, said particles comprising a material light-colored ceramics including white ceramics and having Vickers hardness of not less than 200 Hv; and an oil having a viscosity of 5,000 centipoises to 15,000 centipoises;
- 10 wherein said particles and said oil are mixed with each other.

Application Serial No. 10/563,412 Response to Office Action

Claim 10 (Canceled).

 (Previously Presented) A paste according to claim 9, wherein said oil comprises silicone grease.

Claim 12 (Canceled).